

ANA2124T-PF36

4.0 Megapixel 1080P IR Bullet Fixed Camera



Main Features

- 1/3" 4MP CMOS
- Max 30fps@4MP
- HD and SD output switchable
- 3.6mm fixed lens (2.8mm, 6mm optional)
- Max. IR length 30m, Smart IR
- IP67, DC12V

Camera

Image Sensor	1/3" 4MP C MOS
Effective Pixels	2688(H)×1520(V), 4.1MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s
Minimum Illumination	0.03Lux/F2.0, 30IRE, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	up to 30m (98ft)
IR On/Off Control	Auto / Manual
IR LEDs	18

Lens

Lens Type	Fixed lens/Fixed Iris
Mount Type	Board-in
Focal Length	3.6 mm fixed lens (2.8mm, 6mm optional)
Max Aperture	F2.0
Angle of View	H: 84.8° (99.7°/52.5°/32.9°)
Close Focus Distance	1100mm (800mm/2200mm/4000mm) 43.3" (31.5"/86.6"/157.5")

PAN/TILT/ROTATION

Pan/Tilt/Rotation	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°
-------------------	---

VIDEO

Resolution	4MP (2560×1440)
Frame Rate	25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-Language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
White Balance	Auto/ Manual
Gain Control	AGC
Noise Reduction	2D
Smart IR	Auto/ Manual

ELECTRICAL

Power Supply	12V DC \pm 25%
Power Consumption	Max 4.6W (12V DC, IR on)

ENVIRONMENTAL

Operating Conditions	40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH
Storage Conditions	40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH
Ingress Protection & Vandal Resistance	IP67