

ANA3614T-PF36

4.0 Megapixel 1080P Plastic Dome Camera



Better Security,
Better World.



Main Features

- 1/3" 4MP CMOS
- Max 30fps@4MP
- HD and SD output switchable
- 3.6mm fixed lens (2.8mm, 6mm optional)
- Max. IR length 20m, Smart IR
- DC12V

Camera

| | |
|--------------------------|---|
| Image Sensor | 1/3" 4MP CMOS |
| Effective Pixels | 2688(H)×1520(V), 4.1MP |
| Scanning System | Progressive |
| Electronic Shutter Speed | PAL: 1/25~1/100000sNTSC: 1/30~1/100000s |
| Minimum Illumination | 0.03Lux/F2.0, 30IRE, 0Lux IR on |
| S/N Ratio | More than 65dB |
| IR Distance | up to 20m (66ft) |
| IR On/Off Control | Auto / Manual |
| IR LEDs | 12 |

Lens

| | |
|----------------------|---|
| Lens Type | Fixed lens/Fixed Iris |
| Mount Type | Board-in |
| Focal Length | 3.6 mm fixed lens (2.8mm, 6mm optional) |
| Max Aperture | F2.0 |
| Angle of View | H: 84.8° (99.7°/52.5°) |
| Close Focus Distance | 1100mm (800mm/2200mm) 43.3" (31.5"/86.6") |

PAN/TILT/ROTATION

| | |
|-------------------|---|
| Pan/Tilt/Rotation | Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360° |
|-------------------|---|

VIDEO

| | |
|-----------------|---|
| Resolution | 4MP (2560×1440) |
| Frame Rate | 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P |
| Video Output | 1-channel BNC high definition video output / CVBS video output (Can switch) |
| Day/Night | Auto (ICR) / Manual |
| OSD Menu | Multi-Language |
| BLC Mode | BLC / HLC / DWDR |
| WDR | DWDR |
| White Balance | Auto/ Manual |
| Gain Control | AGC |
| Noise Reduction | 2D |
| Smart IR | Auto/ Manual |

ELECTRICAL

| | |
|-------------------|--------------------------|
| Power Supply | 12V DC \pm 25% |
| Power Consumption | Max 3.2W (12V DC, IR on) |

ENVIRONMENTAL

| | |
|----------------------|--|
| Operating Conditions | 40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH |
| Storage Conditions | 40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH |